

# Compression & Push fit type Fittings

Type: Coupler, Bend, Tee, MTA, MTE, End Cap



90° Male Threaded Elbow



End Cap



90° T Coupling



90° Elbow Coupling



Male Threaded Adapter



Coupling

## Compression fittings

### Application

- Simplest & fastest way to Joints Pipes
- No Fusion Welding
- No Electricity required

## Push fittings

### Features

- Threads: Male threaded BSP.
- Range: 25mm OD, 32mm OD
- Body, Cap, Inner Bush made of Polypropylene with master batch & UV stabilized.
- Gripper made in Acetal (Delrin).
- O-ring made of Nitrile.
- High impact resistant.
- Excellent sealing at min pressure.
- Pushfit type Compression fitting involved two parts to join pipe.

#### Pressure Rating

- Compression type: PN: 6.0 Kg/cm<sup>2</sup>
- Pushfit type: PN: 4.0 Kg/cm<sup>2</sup>
- Compression fittings are tested at 1.6 times of rated pressure in ambient as well as 60° C temperature.

Product Description	Compression Type		Pushfit Type
	25mm OD	32mm OD	32mm OD
Male Threaded Adopter	25 x ¾"	32 x 1"	32 x 1"
Straight Coupler	25 x 25	32 x 32	32 x 32
Male Threaded Elbow	25 x ¾"	32 x 1"	32 x 32
Coupling Elbow	25 x 25	32 x 32	
Tee	25 x 25 x 25	32 x 32 x 32	
Male threaded Tee	25 x 25 x ¾"	32 x 32 x ¾"	
Terminal End	25 x Plug	32 x Plug	32 x Plug



**AUTOMAT IRRIGATION PVT.LTD.**

Website: [www.automatworld.com](http://www.automatworld.com) | e-mail: [contactus@automatworld.com](mailto:contactus@automatworld.com)

YouTube <https://www.youtube.com/automatindustries>

Facebook <https://www.facebook.com/automatindustries>