

Aqua Spray

HT - 203



Application

- For overhead under canopy irrigation in Banana, Palm, Orchards, nurseries, Green houses and hanging on string for vegetable crops irrigation.


Specification

- Sturdy Structure and User Friendly
- Flow Rates: 26-181 L/H
- Good distribution at Low Pressure Operating of 0.5 kg/cm².
- Range of operating Pressure: 0.5 - 2.5kg/cm²
- Quick-threaded /Barbed /female pushfit (6mm) connections are available.
- Excellent Distribution uniformity ranging from Spacing :2 x 2, 3 x 3, 4 x 4 mtr.

Performance Chart

Nozzle Color	Nozzle size (mm)	Pressure (kg/cm ²)	Flow Rate (l/h)	Swivel Color (Black)
				Diameter mtr
Blue	1.0	0.5	26	4.4
		1.0	37	5.5
		1.5	45	6.0
		2.0	52	6.5
		2.5	58	7.0
Green	1.2	0.5	38	5.0
		1.0	54	6.5
		1.5	66	7.0
		2.0	76	7.4
Red	1.4	2.5	85	7.8
		0.5	51	5.2
		1.0	72	7.2
		1.5	88	7.5
Violet	1.8	2.0	102	7.8
		2.5	114	8.0
		0.5	81	5.2
		1.0	115	7.5
		1.5	140	7.8
		2.0	162	8.2
		2.5	181	8.6

* Performance data are obtained under ideal test conditions at 25cm riser height above ground



Assembly/Exploded View

Parts	Parts Description	Material
1	Body	Polyacetal (POM)
2	Swivel	Nylon
3	Nozzle	Polyacetal (POM)



AUTOMAT IRRIGATION PVT.LTD.

Website: www.automatworld.com | e-mail: contactus@automatworld.com



<https://www.facebook.com/automatindustries>



<https://www.youtube.com/automatindustries>